

# MATERIAL SAFETY DATA SHEET

# **Centrament Proof CWP**

# **1. PRODUCT AND COMPANY INFORMATION**

Manufactured / Distributed by

MC-Bauchemie Manufacturing PLC. P.O. Box 5452 Addis Ababa, Ethiopia Addis Ababa, Ethiopia Tel: +251 11 5544334 Tel: +251 11 5544557/8 Fax: +251 11 5543610 www.mc-bauchemie.com Email: ethiopia@mc-bauchemie.com

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS no.	Weight %
OPC	65997-15-1	45 – 55%
Sand	14808-60-7	20 – 30%
Sodium Silicate	1344-09-8	5 – 15%
Lime	1305-62-0	5 - 10%
Sodium Carbonate	497-19-8	5 - 15%

### 3. HAZARDS

### **Emergency Overview:**

This product is irritating to the eyes, respiratory system and skin. Causes burns to the skin and eyes when mixed with water.

### **Potential Health Effects: Eyes**

This product is irritating to the eyes. Symptoms can include irritation, redness, scratching of the cornea, and tearing. Rubbing may cause abrasion of cornea.

### **Potential Health Effects: Skin**

This product is irritating to the skin. Mechanical rubbing may increase skin irritation.

### **Potential Health Effects: Ingestion**

Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

### **Potential Health Effects: Inhalation**

This product is irritating to the respiratory system. Chronic lung disease (silicosis) and/or lung cancer may result from prolonged/repeated breathing of the dust of this material. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

### Medical Conditions Aggravated by Exposure

Hypersensitivity to product, allergies, and skin or respiratory disorders

### 4. FIRST AID MEASURES

Eye contact	If the eyes are contaminated, flush them without delay with large amounts of clean water for at least 15 minutes and get medical attention promptly.	
Skin contact	If skin contact occurs, wipe clean the skin immediately with paper towels and wash immediately with a commercial skin cleaner or with liquid soap and plenty of warm water. Any contaminated clothing, shoes, should be removed and not re- used until clean of resin. Any injuries or irritation that may occur should receive prompt medical attention.	
Inhalation	Not normally applicable. Remove person to fresh air. Obtain	

# MC FOR Buildings



Ingestion

Suitable Extinguishing Media Extinguishing Media not to be used Combustion products

5. FIRE FIGHTING AND MEASURES

# 6. ACCIDENTAL RELEASE MEASURES

After spillage / leakage

Do not induce vomiting, give one pint of water or milk and obtain medical attention without delay.

Foam, carbon dioxide, dry powder Water jet Not applicable

medical assistance if symptoms persist.

Take up mechanically or with an absorbent material e.g. sand, sawdust and collect in a disposal bag.

Do not discharge into drains/surface water/groundwater Please refer to local rules and regulations for disposal.

## 7. HANDLING AND STORAGE

Protective measures

Avoid dust formation. Wear dust mask. Store containers tightly sealed in dry, well ventilated area.

# 8. PERSONAL PROTECTION / EXPOSURE CONTROLS

Personal protective equipments Other	Gloves, safety goggles, dust mask must be worn Chemical resistant apron, face shield, safety helmets, boots, etc must be worn while handling and proper precautions
	should be taken.
Industrial hygiene	Do not use solvent to clean the skin, use industrial skin cleansers or liquid soap and warm water, dry with paper towels not cloth towels. Do not smoke in working area.
	Remove contaminated clothing and launder before reuse. Always work in well-ventilated areas.
	Observe good housekeeping and general hygiene guidelines.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Powder
Color	Grey
Odor	Odorless
Change in physical state	No statement possible
Bulk density	1200 +/-100 kg/m <sup>3</sup>
Wet Density	1.7 +/- 0.05 kg/ltr
Melting Point	N/A
Solubility in water	Partially soluble
рН	Alkaline
Flash Point	N/A

# **10. STABILITY AND REACTIVITY**

Conditions to avoid
Substance to avoid
Hazardous reactions
Thermal Decomposition
Oxidizing properties

# **11. INFORMATION ON TOXICITY**

Information of toxicity in general

Avoid dust formation. Avoid Humidity. Strong acids Stable if store and handled as per section 7 None None

Can cause nuisance dust in dry powdered form. Risk of sensitization, which may lead to allergic dermatitis.



Persons with a history of skin allergies or a tendency towards dermatitis should not handle such products.

# 12. INFORMATION ON ECOLOGICAL EFFECTS

General information

### 13. DISPOSAL

Disposal

14. TRANSPORT

TDG IMDG Code ICAO / IATA UN No.

## 15. REGULATIONS

Labelling Symbol R Phrases

S Phrases

# **16. FURTHER INFORMATION**

Further information

Do not discharge the material into drains, sewers, etc.

Dispose empty bags and surplus material to a place as accepted by builders. Do not incinerate. Attention is drawn to the Control of Pollution Act 1974, the provision of which are enforced by local authorities.

Not classified as dangerous good under transport regulations Not classified as dangerous good under transport regulations Not classified as dangerous good under transport regulations N/A

### None

R36/37 Irritating to eyes and respiratory system
R43 May cause sensitization to skin contact
S26 in case contact with eyes, wash immediately with water and soap.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.

All statements are based on our experience to date. Form based on DIN 52900.

The information shown is based on our experience to date and is true to the best of our knowledge. Any recommendation or suggestions made are without any guarantee. No responsibility is accepted that the information herein is sufficient or correct in all cases.